

DESCRIPTION:

The DPA range digital class-D power ampli¬fier is of switching power technology, which features of minimum power consumption and much higher efficiency up to 85%, moreover it helps to save installation rack space, generate less heat so as to extend its performance life span as a result.

The DPA240N is of rated power output at 240W, so it could be used as digital public address system at minimum cost. The versatile loudspeaker outputs of both high impedance 100V & low impedance 4-16ohms enable it meet both PA fixed installation and Hi-¬ stereo sound installation jobs.

There are one balanced inputs by phoenix connector with gain control. Speaker outputs both by 100V & 4-16ohms. The built-in high-pass ¬alters could be enabled or disabled through the dip switch pre-setting.

Automatic standby enable after no detection of signal input for one minute, immediately wake up at sight of any input. Visual working status indicators include protection, clip, input and output for easy supervision. With complete short circuit, overload, high temp, clip and DC protection.

FEATURE:

- $\sqrt{\text{Class-D PA power amplifi}}$ er of minimum power consumption
- $\sqrt{}$ Less rack space and less heat generation
- $\sqrt{\text{Single channel power ampli}}$ fier into 19" rack mount unit
- $\sqrt{\text{Rated power output at 240W}}$
- √ Speaker outputs 4-16 /100V
- $\sqrt{}$ Balanced XLR input by phoenix connector
- $\sqrt{}$ Each input with separate gain control.
- $\sqrt{}$ Each channel with high-cut \neg alter.
- $\sqrt{}$ Built-in auto standby feature to save power consumption
- $\sqrt{1}$ Separate indicators for protection, clip, input and output
- $\sqrt{}$ Complete short circuit, overload, high temp, clip and DC protection
- $\sqrt{}$ Wide AC input switchable between 115V and 230V
- $\sqrt{24V}$ DC input as option at order request.

As per our company policy one of the constant Product improvement the right is there for reserved to modify product specifications without prior notice

HEINRICH LIMITED, 71-75 SHELTON STREET COVENT GARDEN LONDON T: +442032860291 W: www.heinrichlimited.com E: info@heinrichlimited.com

Class-D Single Channel 240W Power Amplifier



SPECIFICATION:

HEINRICH

Modal	DPA 240 N
Description	Class -D Single Channel 240W Power Amplifier
Rated power	240W
Speaker Output	4-16 Ω & 100V
Frequency Response	L/H Cut OFF 20Hz - 20KHz (+1/-2dB)
	L/H Cut OFF 20Hz - 20KHz (+1/-2dB)
Input	0.775V, 0dBu, balanced phonenix connector
Input Impedance	10ΚΩ
THD	<0.1%(1KHz/-3dBv,100W)
S/N Ratio	>80dB
Crosstalk	>60dB, 1KHz, Max Output
Power consumtion	420W
Power Supply	AC input switchable between 115V & 230V , 50-60Hz
	24V DC input as option at order request.
Dimenstion	482 (w) x 420 (D) x 44 (H) mm
Weight	4.5 kg

As per our company policy one of the constant Product improvement the right is there for reserved to modify product specifications without prior notice

HEINRICH LIMITED, 71-75 SHELTON STREET COVENT GARDEN LONDON T: +442032860291 W: www.heinrichlimited.com E: info@heinrichlimited.com