

IP- Outdoor Bullet Camera 1.3 MP Series

HC-IP103B



DESCRIPTION:

The HC-IP103B network camera is fully compliant implementation of H.264 (MPEG 4, Part 10) provides 1280x960 pixel resolution at full video frame rates of 30 frames per second (fps). The HC-IP103B camera line provides an all-in-one solution with Integrated 720p HD camera, IR illuminator, IR corrected lens, WDR, High Light Compensation and aluminium sleek Dome enclosure with IP66 weatherstandard.

FEATURE:

- Full HD IP megapixel bullet camera.
- True day-night functionality with ICR.
- Smart IR.
- Dual encorder H.264/H.265/MJPEG.
- IP 66 weather proof housing.
- ONVIF compliance.
- Low power consumption.
- Seamless integration with 3rd party NVR's/VMS.

IP- Outdoor Bullet Camera 1.3 MP Series

SPECIFICATION:

Camera Type	
Indoor/Outdoor	IP Outdoor
Image Sensor	1/3" 1.3 MP CMOS
Scanning System	Progressive
Effective Pixels	1280 (H) x 960(V)
Electronic Shutter Speed	Auto/Manual, 1/3(4)~1/100000s
Image Compression	H.264 / M-JPEG
Minimum Illumination	0.02 Lux(Color)/F1.2 0 Lux (IR On)
S/N Ratio	More than 50dB
IR Distance	Distance upto 20 mtr
IR On/Off	Auto
Lens	
Lens Type	Fixed
Focal Length	3.6mm
Max. Aperture	F1.2
Close Focus Distance	0.5 mtr
Auto-Iris	Yes
Video	
Compression	H.264/M-JPEG
Streaming	Dual
Resolution	1.3MP/720P/D1
Auto-Iris	Yes
Frame Rate	Max 1.3MP @ 30fps
Day/Night	Auto(ICR)/Color/B/W
BLC Mode	BLC/HLC
WDR	DWDR
White Balance	Auto/Natural/Manual
Gain Control	Auto/Natural
Noise Reduction	3D DNR
Motion Detection	ON/OFF

IR	Smart IR
Web Viewer	Mozilla Firefox: 7 or above (streaming only) Chrome: 17 or above (streaming only) Internet Explorer 7.x, 8.x, 9.x, 10, 11
Image Setting	Saturation, brightness, sharpness, contrast, sharpness adjustable through client software or web browser
On Screen Display Protocol	Yes (optional)
Protocol	TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, NTP, UPnP,
ONVIF Support	Yes
Communication Interface	1 RJ45 10M / 100M ethernet port
Audio	
Built in microphone	Yes (optional)
Audio in	Yes (optional)
Audio out	Yes (optional)
2-way Audio	Yes (optional)
Audio Codec	G.711
Power Supply	
Power	12V DC/ PoE (802.3af)
Power Consumption	6W Max
Enviornmental	
Ingress Protection	IP 66
Vandal Resistance	
Operating Conditions	(-)10°C to +50°C
Construction	Metallic
Test Stanadard	
EMC Standard	
Warranty	*2 year