

IP- Indoor/Outdoor Dome Camera 2.4 MP Series

HC-IP204D1



DESCRIPTION:

The HC-IP204D1 network camera is fully compliant implementation of H.264 (MPEG 4, Part 10) provides 1920x1080 pixel resolution at full video frame rates of 30 frames per second (fps). The HC-IP204D1 camera line provides an all-in-one solution with integrated 1080p full HD camera, IR illuminator, IR corrected lens, WDR, High Light Compensation and aluminium sleek Dome enclosure with IP 65 & IK 10 weather standard.

FEATURE:

- Full HD IP megapixel bullet camera.
- True day-night functionality with ICR.
- LED IR.
- Dual encoder H.264/MJPEG.
- Fixed lens 3.6 mm.
- IP65/IK10 weather proof housing.
- ONVIF compliance.
- Low power consumption.
- Seamless integration with 3rd party NVR's/VMS.

IP- Outdoor Dome Camera 2.4 MP Series

SPECIFICATION:

Camera Type	
Indoor/Outdoor	IP Indoor/Outdoor Dome
Image Sensor	1/2.9" 2.4 MP CMOS
Scanning System	Progressive
Effective Pixels	1920 (H) x 1080(V)
Electronic Shutter Speed	Auto/Manual, 1/3(4)~1/100000s
Image Compression	H.264 / M-JPEG
Minimum Illumination	0.02 Lux(Color)/F1.2 0 Lux (IR On)
S/N Ratio	More than 50dB
IR Distance	Distance upto 25 mtr
IR On/Off	Auto
Lens	
Lens Type	Fixed
Focal Length	3.6mm
Max. Aperture	F1.2
Close Focus Distance	0.5 mtr
Auto-Iris	Yes
Video	
Compression	H.264/M-JPEG
Streaming	Dual
Resolution	1080P/1.3MP/720P/D1
Auto-Iris	Yes
Frame Rate	Max 1080P @25fps
Day/Night	Auto(ICR)/Color/B/W
BLC Mode	BLC/HLC
WDR	DWDR
White Balance	Auto/Natural/Manual
Gain Control	Auto/Natural
Noise Reduction	3D DNR
Motion Detection	ON/OFF
IR	LED

Web Viewer	Mozilla Firefox: 7 or above (streaming only) Chrome: 17 or above (streaming only) Internet Explorer 7.x, 8.x, 9.x, 10, 11
Image Setting	Saturation, brightness, sharpness, contrast, sharpness adjustable through client software or web browser
On Screen Display Protocol	Yes (optional) TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, NTP, UPnP,
ONVIF Support	Yes
Communication Interface	1 RJ45 10M / 100M ethernet port
Audio	
Built in microphone	Yes (optional)
Audio in	Yes (optional)
Audio out	Yes (optional)
2-way Audio	Yes (optional)
Audio Codec	G.711
Power Supply	
Power	12V DC/ PoE (802.3af)
Power Consumption	7W Max
Enviornmental	
Ingress Protection	IP65 & IK 10
Vandal Resistance	
Operating Conditions	(-)10°C to +50°C
Construction	Metallic
Test Stanadard	
EMC Standard	
Warranty	*2 year

Disclaimer: Product's casing and specification subject to change without any prior notice.