

IP- Indoor/Outdoor Dome Camera 5 MP Series

HC-IP500D



DESCRIPTION:

The HC-IP500D network camera is fully compliant implementation of H.264 (MPEG 4, Part 10) provides 2592x1944 pixel resolution at full video frame rates of 30 frames per second (fps). The HC-IP500D camera line provides an all-in-one solution with integrated 1080p full HD camera, IR illuminator, IR corrected lens, WDR, High Light Compensation and aluminium sleek Dome enclosure with IP65 & IK10 weatherstandard.

FEATURE:

- Full HD IP megapixel dome camera.
- True day-night functionality with ICR.
- Long range smart IR.
- Dual encoder H.264/H.265/MJPEG.
- Varifocal motorized lens.
- IP 66/IK10 weather proof housing.
- ONVIF compliance.
- Low power consumption.
- Seamless integration with 3rd party NVR's/VMS.

IP- Indoor/Outdoor Dome Camera 5 MP Series

SPECIFICATION:

Camera Type	
Indoor/Outdoor	IP Indoor/Outdoor Dome
Image Sensor	1/1.8" 5 MP Sony CMOS Sensor
Scanning System	Progressive
Effective Pixels	2592 (H) x 1944(V)
Electronic Shutter Speed	Auto/Manual, 1/3(4)~1/100000s
Image Compression	H.265/H.264 / M-JPEG
Minimum Illumination	0.02 Lux(Color)/F1.2 0 Lux (IR On)
S/N Ratio	More than 50dB
IR Distance	Distance upto 30 mtr
IR On/Off	Auto
Lens	
Lens Type	Vari Focal
Focal Length	2.8~12mm
Max. Aperture	F1.2
Close Focus Distance	0.5 mtr
Auto-Iris	Yes
Video	
Compression	H.265/H.264/M-JPEG
Streaming	Dual
Resolution	5MP/4MP/1080P
Auto-Iris	Yes
Frame Rate	Max 5MP @20fps
Day/Night	Auto(ICR)/Color/B/W
BLC Mode	BLC/HLC
WDR	True WDR
White Balance	Auto/Natural/Manual
Gain Control	Auto/Natural
Noise Reduction	3D DNR
Motion Detection	ON/OFF
Smart IR	Yes

Web Viewer	Mozilla Firefox: 7 or above (streaming only) Chrome: 17 or above (streaming only) Internet Explorer 7.x, 8.x, 9.x, 10, 11
Image Setting	Saturation, brightness, sharpness, contrast, sharpeness adjustable through client software or web browser
On Screen Display	Yes (optional)
Protocol	TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, NTP, UPnP,
ONVIF Support	Yes
SD Card Support	Optional 32GB
Communication Interface	1 RJ45 10M / 100M ethernet port
Audio	
Built in microphone	Yes (optional)
Audio in	Yes (optional)
Audio out	Yes (optional)
2-way Audio	Yes (optional)
Audio Codec	G.711
Power Supply	
Power	12V DC/ PoE (802.3af)
Power Consumption	6W Max
Enviormental	
Ingress Protection	IP 65 & IK10
Vandal Resistance	
Operating Conditions	(-)10°C to +50°C
Construction	Metallic
Test Stanadard	
EMC Standard	
Warranty	*2 year

Disclaimer: Product's casing and specification subject to change without any prior notice.