

All Weather Environmental Speaker (30W)

HSK30/TW



Feature

Commercial PA system wall mount speaker with transformer. All weather speaker for indoor & outdoor sound system. Ideal for school, office, hotel and airport background music system. Economy rang fashion wall mount cabinet loudspeaker. Rated power output 30W at 100V. All HEINRICH loudspeaker have undergone through testing procedure to ensure that all products compliance with LOW VOLTAGE DIRECTIVE (BS EN 60065, 2003) and EMC (BS EN 61000-6-Part 1/2/3/4). Weather-resistant brackets and hardware withstand the rigors of year-round outdoor ABS enclosure and Galvanized powder coated steel grille in white. Line Input 100V/70V.

Specifications

Model	HSK30/TW
Description	All Weather Environmental Speaker
Rated Power Output	30W
Line Input	100V or 70V
Frequency Response	90-20KHz
SPL(@1W/m)	94dB (1KHz, +/-3dB)
Speaker Unit	5" woofer and 2x2.5" tweeter & middle three way speaker units
Dimension	290x190x122mm
Material	ABS enclosure and Galvanized powder coated steel grille in white
IP Rate	IP55
Working Condition	Designed to withstand: – salt fog, sun, high humidity: 100%RH – temperature extremes: -40°C to +70°C
Opening Angle	1kHz/4kHz (-6dB) Horizontal: 185°/115° Vertical: 178°/93°
Mounting Way	Quick installation by supplied stainless mounting bracket
Weight	2.5kg

All Weather Environmental Speaker (30W)

Frequency Response VS SPL Diagram

