

# PP SERIES AMPLIFIER WITH SWITCH POWER SUPPLY

PPSERIES



## Special point

PP series amplifier are with switch power supply. Its compact and precise structure makes it high-performance. Each channel has independent adjustable peak output voltage. Which enables the amplifier to drive speakers with different power easily. Intelligent protecting circuit provides advanced technology to protect the internal circuits and connected lods, so that the amplifiers and speakers can still be operated in extreme conditions .

Applied to big performance, stadium, high class commercial recreation alub. Etc.

## Specification

Model	PP10000	PP7000	PP9000	PP14000
8 ohms Stereo power	4x1300W	2x1450W	2x1600W	2x2350W
4 ohms stereo power	4x2100W	2x2800W	2x3000W	2x4400W
2 ohms stereo power	4x2500W	2x3500W	2x4500W	2x7000W
8 ohms Bridge power	2x4200W	5600W	6000W	88000
4 ohms Bridge power	2x5000W	7000W	9000W	14000W
Frequency Response (1W/8Ω) + 0/3-dB	6.8Hz-34KHz	6.8Hz-34KHz	2Hz-34. 2KHz	2Hz-34. 2KHz
Input impedance	20k0hm			
THD 20 Hz-20KHz for 1W	<0.1%			
Signal-to-Noise Ratio	>112dB			
Channel separation (Crosstalk) at 1 KHz	>70dB			
Voltage Gain (dB)	23,26,29,32,35,38,41,44dB selectable			
Input Connectors (per channel)	3-pin XLR, electronically balanced			
Output Connectors (per channel)	Neutrik Speakon or Binding Posts			
Cooling	Front-to-rear airflow, temperature controlled speed			
Amplifier Protection	Short circuit,open circuit,direct voltage,high temperature,radio-frequency, ultralow frequency, current peak limitery.			
Dimensions (WxHxL) (mm)	88x483x483			
Packing dimension (WxHxL)(mm)	180x560x500			
Net weight	12kg			
Gross weight	13.4kg			

HEINRICH

HEINRICH LIMITED, 71-75 SHELTON STREET COVENT GARDEN LONDON  
T: +442032860291 W: www.heinrichlimited.com E: info@heinrichlimited.com