

Digital Conference System

CE1500



Description:

This system designed by the latest digital technology in accordance with IEC914 and ISO standards. It's a high effective Multi-functional meeting system for a meeting or conference, and it's easy to setting-up, debugging and using without training. The main unit can match the request no matter for few of representative delegate units in the small conference system, or the big conference system includes interpreter equipment, hundreds of representative units or wired and wireless language distribution equipments. The main unit has all the power supply for all of representative units and basic controlled function, and has port which connected with kind of other equipments. Also, it can reach much more function by adding other equipments and software

Feature:

Main Unit :

- Power consumption of main unit : 450W
- Each unit can support 60 units delegate and chairman microphone, it could be extended to support 200 units microphone by adding more Extension power supply unit.
- With four group 8-DIN socket for multi-line connection.
- With one group wired microphone input port, independent volume adjusted.
- High fidelity sound quality.
- With audio input signal and REC output.
- Built-in 2 X 50W amplifier for adjusting volume.
- Built-in 1W monitor loudspeaker volume adjusted.
- System volume independent adjusted.
- With AUX input independent volume adjusted.
- With limit function, "1/2/3/5/free" mode.
- Special "T" type single cable with DIN socket.
- With BAL connected port.
- 220V/50Hz
- N.W :13kg
- External dimensions : 485mm (includes microphone pipe) × 100mm (2U, includes engine case foot pad) × 355mm (W×H×D); It can be put on the table or install in the 19inch standard frame.
- This system can be used with automatic video camera tracking system and voting system.

Digital Conference System

Extension Unit Function :

When the Conference Speaker Unit Reaches 60 Sets, It Needs the Extension Unit for Supplying the Power:

- Power Consumption: 450W.
- With Four Group 8-DIN Socket for Multi-Line Connection.
- 220V/ 50Hz
- External Dimensions : 485mm (Includes Microphone Pipe) × 100mm (2U, Includes Engine Case Foot Pad) × 355mm (W×H×D) ; It Can Be Put on The Table or Install in the 19inch Standard Frame.

Specification:

Model	CE1500
Power Consumption	450W
Frequency Response	20Hz - 20KHz
Amplifier	2 X 50W
S/N Ratio	>95dB
T.H.D	<0.1%
Follow Specification	IEC60914
Signal-Noise Ratio	>95dB(A)
Speaker	1W Buit in
Microphone Input	4 Group 8 DIN Socket
Power Supply	220V/50Hz
Dimensions (WxHxD)	485mm X 100mm X 355mm
Net Weight	13Kg