

# Class-D Four Channel 240W Power Amplifier

DPA4240



## DESCRIPTION:

The DPA range digital class-D power amplifier is of switching power technology, which features of minimum power consumption and much higher efficiency up to 85%, moreover it helps to save installation rack space, generate less heat so as to extend its performance life span as a result.

The DPA-4240 is of rated power output at 4 x 240W, so it could be used as digital public address system at minimum cost. The versatile loudspeaker outputs of both high impedance 100V & low impedance 4-16ohms enable it meet both PA fixed installation and Hi-fi stereo sound installation jobs.

There are one balanced inputs by phoenix connector with gain control. Speaker outputs both by 100V & 4-16ohms. The built-in high-pass filters could be enabled or disabled through the dip switch pre-setting.

Automatic standby enable after no detection of signal input for one minute, immediately wake up at sight of any input. Visual working status indicators include protection, clip, input and output for easy supervision. With complete short circuit, overload, high temp, clip and DC protection.

All DPA Range Amplifier is EN54 Approved

## FEATURE:

- Switching power technology digital power amplifier
- Class-D PA power amplifier of minimum power consumption
- Less rack space and less heat generation
- Multi channel power amplifier into 19" rack mount unit
- Rated power output at 4 x 240W
- Speaker outputs 4-16 /100V
- Balanced XLR input by phoenix connector
- Each input with separate gain control.
- Each channel with high-cut filter.
- Built-in auto standby feature to save power consumption
- Separate indicators for protection, clip, input and output
- Complete short circuit, overload, high temp, clip and DC protection
- Wide AC input switchable between 115V and 230V
- 24V DC input as option at order request.

As per our company policy one of the constant Product improvement the right is there for reserved to modify product specifications without prior notice

**HEINRICH**

**HEINRICH LIMITED**, 69 Athlone Road London SW22DU  
W: [www.heinrichlimited.com](http://www.heinrichlimited.com) E: [info@heinrichlimited.com](mailto:info@heinrichlimited.com)

# Class-D Four Channel 240W Power Amplifier

DPA4240



## SPECIFICATION:

Model	DPA-4240
Description	Class -D Multi Channel 240W Power Amplifier
Rated power	4 x 240W
Speaker Output	4-16 $\Omega$ & 100V
Frequency Response	L/H Cut OFF 20Hz - 20KHz (+1/-2dB)
	L/H Cut OFF 20Hz - 20KHz (+1/-2dB)
Input	0.775V, 0dBu, balanced phonenix connector
Input Impedance	10K $\Omega$
THD	<0.1%(1KHz/-3dBv,100W)
S/N Ratio	>80dB
Crosstalk	>60dB, 1KHz, Max Output
Power consumption	1127W
Power Supply	AC input switchable between 115V & 230V , 50-60Hz
	24V DC input as op on at order request.
Dimension	482 (w) x 420 (D) x 44 (H) mm
Weight	9 kg

As per our company policy one of the constant Product improvement the right is there for reserved to modify product specifications without prior notice