

EMERGENCY VOICE COMMUNICATION-EVCA2

EVCA2



DESCRIPTION:

The Emergency voice communication unit having inbuilt telephone handset with volume controller for communication purpose during the emergency situation between control room and floor. Unit will support upto 92 zones, it is having inbuilt numerical keypad to support the zone wise/all call selection, reset button, PTT and Listen button for communication purpose. The particular zone will be displayed in the LCD of EVCA2, during communication happening any other zone we can access other zone call also, it will work has conferences system. EVCA2 have magnetic lock door. It is available with surface/table mounted module along with accessories.

FEATURE:

- EVCA2 is an all-in-one Emergency Voice Communication (EVC) system.
- Fully monitored and battery-backed (24 hours quiescent and three hours functional).
- Fully compliant to BS5839-9:2011. Assists companies with compliance to BS9999:2008.
- Remote units are wired in a radial (star) conjunction using two core (fire resisting enhanced/non-enhanced) cable.
- Fully networkable. Networked panels are wired in a loop conjunction using 2 x two core (fire resisting enhanced/non-enhanced) cable.
- In the event of a break in the network loop, the system will continue to function.
- All outstations are powered from the line, including the roaming telephone enclosure and disabled toilet alarms.
- Optional link to fire detection system prevents hoax disabled refuge calls (C2CFPE required). Fire fighter,roaming telephones and toilet alarms remain active.
- Speech steered; disabled refuge outstations.
- Full duplex speech; fire fighter and emergency/steward telephones.
- Any combination of the following outstations can be installed on a single system:
 - Disabled refuge (Type B outstations).
 - Fire fighter telephones (Type A outstations).
 - Steward (emergency) telephones (Type A outstations).
 - Roaming telephones.
 - Disabled toilet alarms.

As per our company policy one of the constant Product improvement the right is there for reserved to modify product specifications without prior notice

EMERGENCY VOICE COMMUNICATION-EVCA2

SPECIFICATION:

Model	EVCA2
Speaker Output	1W
MIC Input Sensitivity	200 ohm
Serial connections	1 RS232 for NEP
Size and Material	Metal enclosure : Surface Mounted - Black RAL 9005 Height x Width x Depth : 300 x 400 x 150mm Weight : 4.5 Kg
Power supply	24V DC

As per our company policy one of the constant Product improvement the right is there for reserved to modify product specifications without prior notice