

IP Networking Classic Intercom Panel

IP-INT1



FEATURES:

- Ideal solution for outdoor or indoor two way communication system in park, school, factory, train station and airport.
- IP network intercom system very suitable for big scale installation system whether by CAT5 cable or fiber optical cable.
- Aluminum finish with damage proof screw fixing up.
- Both surface and embedded mounting ways with supplied mounting box.
- Classic range high quality IP intercom panel.
- Intercom panel built-in speaker and microphone.
- Full duplex two way communication system.
- It can start the communication to the call station by pressing the call button, the call station will be reminded with ring call and indicator as which intercom panel from where is calling. The call will be automatically transferred to next call station once busy, no answer or fault occurred.
- With one contact output and contact input for third party communication.
- Non dedicated network is needed, the system could be easily built-up over exiting LAN/WAN network.
- Embedded server Lynux technology with two ARM and DSP high speech chip.
- Max support 64,000 call stations working at the same time.
- Start time less than 0.1 second.
- Network data delay of less than 100 milliseconds.
- Waterproof rate of IP54.
- It is powered by DC12V, the power adapter is included.

IP Networking Classic Intercom Panel

SPECIFICATION:

Model	IP-INT1
Description	IP Network Classic Intercom Panel
Mounting	Support both surface or embedded by supplied mountingbox
Power Supply	DC 12V
Power Consumption	5W
Network Protocol	TCP, UDP, ARP, ICMP, IGMP
Network Speed	10/100Mbps
Audio Sampling	8KHz-44.1KHz, 16 bits
Transmission Rate	8Kbps to 320Kbps
S/N Ratio	≥90dB
Frequency Response	20Hz-20KHz
Data Delay	100 milliseconds
Waterproof Rate	IP54
Connector	One line output & one RJ45 port for LAN, one contact input and one contact output
Dimensions	255(W)×115(D)×50(H)mm