

# The Chairman/Delegate on Behalf of the Unit

MC150C  
MC150D



## Feature:

### Delegate Microphone :

- Designed in accordance to ISO and IEC914.
- Speaking and listening function.
- The system power supply for all the delegate units is provided by the main unit at 24 safe voltage.
- 8P-DIN plugs for system T-type connection.
- Unidirectional electrets MIC and HIFI voice loud-speaker
- Electric capacity type microphone, equipped with windshield cover.
- Extended pipe optional.
- The annular red indicator lamp could show the state of the microphone.
- The microphone has a speaking button and indicator lamp; it can control the state of speech.
- Equipped with an earphone output jack and REC output jack.
- All the loudspeakers will be under idle state simultaneously when microphone is on and the red indicators will light
- Auto-off function: The microphone would close automatically in 30 seconds after making a speech.
- Built-in video tracking.

### Chairman Microphone:

**Including the functions of the delegate unit, chairman unit has other following functions:**

- The chairman unit number in the system is unrestricted, can join in any position of the system.
- Equipped with an earphone output jack and wireless MIC input jack
- Turn down delegate MIC by press the priority button.
- Indicative sound for chairman unit (optional)

# The Chairman/Delegate on Behalf of the Unit

## Specification:

Model	MC150C & MC150D
Power Supply Mode	Host Power Supply
Color	Black
Output	Earphone output jack ad REC output jack
Connector	8P-DIN
T.H.D	<0.1%
Follow Specification	IEC60914
Signal-Noise Ratio	>95dB(A)
Dynamic Range	>90dB
Power Dissipation	1.8W
SPL Max SPL	125dB (THD>3%)
Microphone Input Impedance	1K $\Omega$
Sensitivity	-46dBV/Pa
Frequency Response	20Hz-20KHz
Weight	0.7Kg
Microphone Stem Height	420mm (as per requirment)
Installation Mode	Embedded
The size (length x width x depth)	230x110x70mm