

IP Networking Remote Microphone (Touch Screen)

PM8-F



FEATURES:

- Touch screen IP remote microphone, with exquisite appearance, elegant craft and modern design.
- Full duplex two way communication between different remote microphones.
- Embed PC technology, built-in DSP & high speed industrial chip to ensure start time less than 1 second.
- With 7 inch LCD user-friendly human-machine interface(Touch Screen)
- Support Two MIC intercom without server.
- Several paging capacity: zone paging, group paging, all zone paging, two way intercom.
- Built-in 3W full-range monitor speakers with clear voice restoration and no echo noise.
- With SD input to broadcast pre-recorded voice message and BGM to different zones.
- Enable to transmit local sources to be broadcasted over network.
- Within one microphone input and one line input and one line output for sound system.
- 24V DC power supply, the power adapter is included in the packaging.
- Support DHCP, no need to set IP address

SPECIFICATION:

Model	PM8-F
Description	IP Network Remote Microphone (Touch Screen)
Communication Protocol	TCP/IP, UDP, IGMP, ARP, UDP
Audio Format	MP3/MP2
Sampling Rate	8K~48KHz
Transmission Speed	10M/100Mbps
Frequency Response	20Hz~16KHz (+1dB, -3dB)
T.H.D.	≤0.3%
S/N Ratio	>70dB
Connector	One RJ45 port, one line input, one line output, one mic input, one USB input
Working temp	-5 °C~ +40°C
Humidity	10% ~ 90%
Power Consumption	≤10W
Power Supply	DC 24V
Dimensions	270x150x58mm
Weight	2.2Kg