

Two Way Talk Back Speaker-H2RRG

H2RRG



DESCRIPTION:

HEINRICH make Talk back speaker having inbuilt 6W Speaker, Unidirectional Microphone with pre-amp and Call Button to communicate with main control room during the Emergency condition. It Provide two-way communication between building management and person occupying a 'Refuge Area' During an emergency evacuation - typing a fire. Up to 600 it can communicate with cat6 cable, User simply press the button to initiate call (occupy area). Further Communication is hands free at the refuge point or by the user at the control panel. Calls are reset either at the control panel or via the remote, when the refuge area Occupant has been evacuated to safety. Talk Back unit will support external speaker unit will support external speaker only for one way one way announcement. It can be surface mounted or concealed.

FEATURE:

- Multizone communication and Ease to operate
- Distance more than 700 Metre
- Sound Pressure level 98dB
- Acoustic inside enclose to reduce extra noise
- integration with other system like, fire Alarm, BMS etc.
- polypropylene drive for long lasting

SPECIFICATION:

Model	H2RRG
Power tap@100V	6W
SPL(1W/1M)	90dB
Max. SPL	98dB
Frequency Response	50-18KHz
Input Sensitivity	200 Ohm
S/N Ratio	68dB
Finish	Baffle: MS, Green
Dimension	180 x 140 x 60
Weight	2kg
Mounting	Surface/ Concealed

As per our company policy one of the constant Product improvement the right is there for reserved to modify product specifications without prior notice